

ROAD MASTER C.R

Master Road Master C.R(chlorinated rubber) Road Marking Paint is an acrylic based quick drying paint modified with chlorinated rubber for use on asphalt and concrete road, primarily for curbstones, speed humps or other areas with high traffic.

PRODUCT BENEFITS







EASY TO APPLY



LONG LASTING FINISH



DRYING



PRODUCT FEATURES

WASHABILITY



AVAILABLE PACKS



PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination removed by stiff bristle brushing.



The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc. All traces of release agent must be removed. On chalky and dusty surfaces, all loose material must be removed by stiff bristle brushing.

FINISH



TECHNICAL INFORMATION

Coverage

120-140 sq.ft per Litre

Application

No of Coats

1,00,00

Thinner


- Cleaning
 - Clean all equipment with Thinner
- Drying Time

2-3 hours between coats

Thinning

By Roller / Brush 10-15% By Spray 25%

SPREADING RATE



SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable.

You must wear eye protection while applying paint. Always keep container air tight close.

It must be kept out of children's reach.

Incase of contact with eyes, wash with brimful cup of water and immediately approach doctor.

Always manage container to keep it in upright position.

Protect it from extreme temperatures.

Please do not empty into drain and water sources.

Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.

In case ventilation is insufficient the use of proper respiratory equipment is advised.