

WEATHER RESISTANT



PRODUCT BENEFITS



ANTI-FUNGAL



RESIST HAIRLINE
CRACKING



LOW DIRT
PICKUP




HIGH COLOR
RETENTION



HIGH SCRUB
RESISTANCE

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW

COLOURS AVAILABLE

46

Factory Made Direct Shades

*Light & Pastel shades can be tinted from the Master Paints Colour World outlets



TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

AVAILABLE PACKS



1 Litre

4 Litre

16 Litre

FINISH



PREPARATION REQUIRED



Surface must be clean, dry and free from dust, oil and grease. After priming with Master Exterior Primer, Fill cracks or holes with Master Exterior Wall Putty. To repaint a surface sand it properly before you paint.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper or grinder and dust off.



Can be applied to the following surfaces subject to the surface base preparation for long lasting and good adhesion. Brick, Cement, Bare Timber, MDF, Set Plaster, Fibrous Plaster, Concrete, Masonry, Plasterboard and Brick Block.

TECHNICAL INFORMATION

- Coverage: 12-14 m² / litre / coat
- Application: Brush / Roller / Spray Gun
- Thinner: Clean Water
- Drying Time: 2-3 hours between coats
- No of Coats: 3-4
- Thinning: By Roller / Brush 50-75%
By Spray 25%
- Cleaning: Clean all equipment with Water

SPREADING RATE



2 COAT

On previously painted surfaces to get the one coat hiding up to 100 sq.ft per liter/ per coat



3 COATS

On new surfaces up to 100 sq.ft per liter by two coats

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.
STIR THOROUGHLY BEFORE USE.