

SYNTHETIC ENAMEL

PRODUCT BENEFITS



SMOOTH
FLOW



ANTI-FUNGAL



IMPROVE
COVERING



STAIN
RESISTANT



WIDE
COLOR RANGE



PRODUCT FEATURES

WASHABILITY



✓ **BEST IN CLASS**
HIGH
MEDIUM
LOW

COLOURS AVAILABLE

60

Factory Made Direct Shades



TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces.
(With cracks and other surface defects)

AVAILABLE PACKS



0.91 Litre



3.64 Litre



14.56 Litre

FINISH



SUPERIOR SMOOTH NORMAL LOW

✓ **SMOOTH**

SPREADING RATE



2 COAT

On previously painted surfaces to get the one coat hiding up to 160sqft per liter/ per coat



3 COATS

On new surfaces up to 125 sq.ft per liter by two coats

PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. Scuff surface using abrasive paper and dust off. Use Master Primer Red Oxide on metal surface and under coat on wooden surface and leave to dry.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Use Master Primer Red Oxide on metal surface and under coat on wooden surface and leave to dry.

TECHNICAL INFORMATION

- Coverage
14-17 m² / litre / coat
- Application
Brush / Roller / Spray Gun
- Thinner
White Spirit / Turpentine
- Drying Time
12 hours between coats
- No of Coats
2-3
- Thinning
By Roller / Brush 10-15%
By Spray 25%
- Cleaning
Clean all equipment with Spirit or Turpentine

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable.
You must wear eye protection while applying paint. Always keep container air tight close.
It must be kept out of children's reach.
In case of contact with eyes, wash with brimful cup of water and immediately approach doctor.
Always manage container to keep it in upright position.
Protect it from extreme temperatures.
Please do not empty into drain and water sources.
Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.
In case ventilation is insufficient the use of proper respiratory equipment is advised.
STIR THOROUGHLY BEFORE USE.