



N.C PRIMER

Material Safety Data Sheet

Primer based on nitrocellulose and alkyd resins. It has an optimum balance between standability, water resistance and hold out of top coats.

**Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com**



PRODUCT INFORMATION

Description: Primer based on nitrocellulose and alkyd resins. It has an optimum balance between standability, water resistance and hold out of top coats.

TECHNICAL INFORMATION:

Colour	Grey
Finish	Matt
Generic Type	NC
Vol Solid	40 %
Spreading Rate	13.3 m ² / L. @30 µm dft.
Drying Time	15 min. at 30 °C.
Recoating Time	4 hrs.
Thinner / cleaner	NC Thinner
Weight / Litre	1.30 – 1.4 kg.
Flash Point	40 °F
Further coat	NC topcoats
Packing size	0.91 and 3.64 litres.

APPLICATION DETAIL :

Conventional or airless spray.

TYPICAL SURFACES :

The temperature of the substrate should be min. 3°C above the dew point of the air, temperature and relative humidity not more than 70% measured in the vicinity of the substrate. Good ventilation is necessary when the paint is used in confined spaces. Mix the paint to uniform consistency before application.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

