


Master Luxury Plastic Emulsion

Material Safety Data Sheet

Master Luxury Plastic Emulsion (Acrylic Based) is an exclusive quality emulsion with a soft matt finish. It is absolutely suitable for all interior masonry surfaces.

Research and Development Department
Master Paint Industries (Pvt) Ltd. 14 Egerton
Road.Lahore.Phone :00924 2 – 111 -333 – 465,
E-Mail : info@masterpaints.com
01-Jan-2018



Master Luxury Plastic Emulsion

Material's Technical & Safety Data Sheet

PRODUCT INFORMATION

Description: Master Luxury Plastic Emulsion (Acrylic Based) is an exclusive quality emulsion with a soft matt finish. It is absolutely suitable for all interior masonry surfaces including brick work, plaster, cement rendering and wall boards. It is based on German Technology. It is available in wide range of colours and in new packing that is absolutely matched with international standard.

Recommended Use: It is absolutely suitable for all interior masonry surfaces including brick work, plaster, cement rendering and wall boards.

PHYSICAL CONSTANTS:

Pack Size: 1.00 LTR ,4.00 LTR & 16.00 LTR (Pack)

Finish: Matt

VOC Content: Less than 50g/LTR

Theoretical Spreading rate : 12 to 18Sqmtr/liter/coat (25±5-microns)

Drying time: 2-3 -Hours Between coats

Physical constants are subject to normal manufacturing tolerances

APPLICATION DETAIL :

Application Method : Brush, Roller

Thinner : Clean Water

Thinning : By Roller or Brush 50 – 75%

No. of Coats : 2 to 3 Coats

Cleaning : Clean all equipment with water.

SURFACES PREPRATION

New Surfaces: Surface must be clean, dry and free from efflorescent salts. Prime with Master Primer, after leveling the surface with Master Wall Putty, apply the plastic emulsion.

Previously painted surfaces: Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime with Master Primer, after leveling the surface with Master Wall Putty, apply the plastic emulsion



Use obrasive paper



Dust off



Seal a coat with primer

SAFETY AND ENVIRONMENT NOTES**FIRST-AID MEASURES****GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention immediately!

INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure Breathing can take place.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to Hospital or eye specialist.

FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Beware, risk of formation of toxic and corrosive gases.

SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

Self-Life of product is 03 year (Keep in shade) (Minimum requirement from PSQCA is 02 years).

STORAGE CLASS

Flammable liquid storage Recommended.

===== OTHER INFORMATION =====
THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE. IT IS TRUE & ACCURATE TO THE BEST OF OUR KNOWLEDGE, BUT IS NOT INTENDED TO BE ALL INCLUSIVE. USERS SHOULD CONSIDER THIS INFORMATION AS A SUPPLEMENT TO OTHER INFORMATION GATHERED BY THEM & MUST MAKE THEIR OWN DETERMINATION OF SUITABILITY & COMPLETENESS TO ASSURE PROPER USE & DISPOSAL.

===== END OF THE REPORT =====

