

2K PREMIUM

A two component Acrylic Polyurethan and Clear Coat Paint giving a high performance finishes.

PRODUCT BENEFITS



WIDE
RANGE



STAIN
RESISTANT



EXCELLENT
GLOSS



LONG TERM
RECOATABLE



FAST
DRYING



PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

FINISH



SHINY

SMOOTH

NORMAL

LOW

✓ SMOOTH

AVAILABLE PACKS



1 Litre



4 Litre

TECHNICAL INFORMATION

● Finish

Gloss

● Generic Type

Polyurethane Coating

● Vol Solid

45%

● Drying Time

2 - 4 hrs. at 30 °C

● Recoating Time

8 - 12 hrs

● Pot Life

1 hrs

● Thinner / Cleaner

PU Thinner

PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of wood grains. Seal with N.C Putty or Maestro Putty.



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Seal with N.C Sealer.

SPREADING RATE



1 COATS

On new surfaces up to 100-120 sq.ft per liter by single coat

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable.

You must wear eye protection while applying paint. Always keep container air tight close.

It must be kept out of children's reach.

Incase of contact with eyes, wash with brimful cup of water and immediately approach doctor.

Always manage container to keep it in upright position.

Protect it from extreme temperatures.

Please do not empty into drain and water sources.

Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.

In case ventilation is insufficient the use of proper respiratory equipment is advised.

APPLICATIONS

Polyurethane Finish is a specialized chemical resistant finish and requires sound preparation and a suitable Priming system to perform to its optimum. It is recommended that potential specifies follow guidelines for preparation from the Data Sheet for the primer system selected.